

# RIB 900

<b>TIRE SIZE</b>	<b>400/60 - 15.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	HEUPRESSE / LANDWIRTSCHAFTLICHE GERÄTE / ANHÄNGER / ERNTEMASCHINE / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS FREE ROLLING</b>	147 A8



## ABMESSUNGEN US STANDARD

<b>USA-CODE</b>	94026340	<b>RC (IN)</b>	100.9
<b>SW (IN)</b>	15.9	<b>RIM REC</b>	AG 13.00
<b>OD (IN)</b>	34.4	<b>ECE</b>	E4-106R-001548
<b>SLR (IN)</b>	15.0	<b>PR</b>	16

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	58
5 FR	9490
15 FR	8070
20 FR	7590
25 FR	6780

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.