


# EARTHMAX SR 468

|              |                                                                                          |
|--------------|------------------------------------------------------------------------------------------|
| TIRE SIZE    | 40.00 R 57                                                                               |
| UM           | IS STANDARD                                                                              |
| CONSTRUCTION |  RADIAL |
| MACHINERY    | STEL DUMPER                                                                              |
| VERSION      | CUT RESISTANT COMPOUND                                                                   |
| TIRE TYPE    | TL                                                                                       |
| LI/SS        | 250 B                                                                                    |



## DIMENSIONER IS STANDARD

|          |           |             |           |
|----------|-----------|-------------|-----------|
| OD (MM)  | 3575      | RIM ALT     | 32.00/6.0 |
| SLR (MM) | 1595      | TRA CODE    | E4        |
| RC (MM)  | 10700     | STAR RATING | ★★        |
| RIM REC  | 29.00/6.0 |             |           |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 5.50  | 5.75  | 6.00  | 6.25  | 6.50  | 6.75  | 7.00  |
|------------|-------|-------|-------|-------|-------|-------|-------|
| 50         | 50000 | 51500 | 53000 | 54500 | 56000 | 58000 | 60000 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.