


# AS 504

<b>TIRE SIZE</b>	<b>9.0/70 - 16</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	TELESKOPLASTARE / ÅKERSLÄP / ARBETSFORDON / TELESKOPLASTARE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	106 A8
<b>LI/SS FREE ROLLING</b>	119 A8



## DIMENSIONER US STANDARD

<b>USA CODE</b>	94048830	<b>RC (IN)</b>	90.0
<b>SW (IN)</b>	8.7	<b>RIM REC</b>	W 7
<b>OD (IN)</b>	29.9	<b>ECE</b>	E11-106R-004536
<b>SLR (IN)</b>	14.0	<b>PR</b>	10

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	64
5 FR	4200
15 FR	3570
20 FR	3360
25 FR	3000
5 DW	2930
15 DW	2490
20 DW	2350
25 DW	2090

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.