

AGRIMAX RT 855

TIRE SIZE	320/85 R 36
UM	IS STANDARD
CONSTRUCTION	
MACHINERY	SPRAYER / VINEYARD HARVESTER / TRACTOR / HARVESTER / IMPLEMENTS
VERSION	STANDARD
TL/TT	TL
LI/SS	147 D ; 150 A8



DIMENSIONS IS STANDARD

SW (MM)	329	RIM REC	W 11
OD (MM)	1458	RIM ALT	W 9 ; W 10
SLR (MM)	672	ECE	E11-106R-003511
RC (MM)	4404	SRI	700

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.4
65	1160	1330	1500	1810	2010	2120	2320	2515	2685	2825	3075
50	1220	1400	1575	1905	2110	2230	2440	2645	2825	2970	3230
40	1270	1455	1645	1985	2200	2325	2540	2755	2945	3095	3350
30	1335	1530	1725	2080	2310	2440	2665	2895	3090	3250	3540
10 LT	1555	1785	2010	2430	2695	2845	3110	3375	3605	3790	4125
10 HT	1335	1530	1725	2080	2310	2440	2665	2895	3090	3250	3540

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.