

AGRIMAX RT 855

TIRE SIZE	320/85 R 38
UM	US STANDARD
MACHINERY	PULVÉRISATEUR / MACHINE À VENDANGER / TRACTEUR / MOISSONNEUSE / OUTILLAGE AGRICOLE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	143 A8/B



DIMENSIONS US STANDARD

CODE USA	94039593	RIM ALT	W 9 ; W 10 ; DW 10 ; DW11
SW (IN)	13.0	ECE	E4-106R-000781
OD (IN)	59.4	TRA CODE	R1W
SLR (IN)	27.6	TREAD DEPTH (32nd)	52.29
RC (IN)	180.3	TMPH (TM/H)	0
RIM REC	W 11		

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	17	23	29	35	41	46	52
30	2170	2520	3310	4030	4390	4700	5110	5530	6000
25	2170	2520	3310	4030	4390	4700	5110	5530	6000
20	2330	2710	3550	4320	4710	5030	5480	5930	6440
5 LT	2910	3390	4440	5400	5890	6290	6860	7420	8060
5 HT	2330	2710	3550	4320	4710	5030	5480	5930	6440

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.