


# AGRIMAX RT 765

<b>TYRE SIZE</b>	<b>280/70 R 18</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTOR / IMPLEMENTS
<b>VERSION</b>	STANDARD
<b>TL/TT</b>	TL
<b>LI/SS</b>	114 A8/B



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94021901	<b>RC (IN)</b>	100.3
<b>SW (IN)</b>	10.8	<b>RIM REC</b>	W 9
<b>OD (IN)</b>	33.4	<b>RIM ALT</b>	W 8 ; W 10
<b>SLR (IN)</b>	15.0	<b>ECE</b>	E4-106R-000635

## LOAD CAPACITY (LBS/TYRE)

MPH / PSI	9	12	15	17	20	23	29	35
<b>30</b>	1220	1410	1620	1830	2040	2240	2420	2600
<b>25</b>	1220	1410	1620	1830	2040	2240	2420	2600
<b>20</b>	1310	1510	1730	1960	2180	2400	2600	2790
<b>5 LT</b>	1640	1900	2170	2450	2730	3010	3250	3490
<b>5 HT</b>	1310	1510	1730	1960	2180	2400	2600	2790

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.