

# PL 801

<b>TIRE SIZE</b>	<b>5.00 - 8</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	ANCINHO ROTATIVO / CEIFEIRA / EMPILHADOR / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS / EMPILHADOR
<b>VERSÃO</b>	STANDARD
<b>TIRE TYPE</b>	TT



## DIMENSÕES IS STANDARD

<b>SW (MM)</b>	135	<b>ECE</b>	E11-106R-003381
<b>OD (MM)</b>	468	<b>PR</b>	8
<b>RIM REC</b>	3.00 D		
<b>RIM ALT</b>	3.25 I		

## LOAD CAPACITY (KG/TIRE)

<b>KM/H / BAR</b>	<b>8.30</b>
<b>25 LOAD WHEEL</b>	1235
<b>25 STEER WHEEL</b>	950
<b>10 OTHER VEHICLES</b>	1235
<b>25 OTHER VEHICLES</b>	950
<b>STATIC SIDE LOADER</b>	1435

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.