


# AGRIMAX V- FLECTO

<b>TIRE SIZE</b>	<b>VF 480/80 R 42 CFO</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTOR / HOCHLEISTUNGSTRAKTOR
<b>VERSION</b>	SPECIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	168 D



## ABMESSUNGEN IS STANDARD

<b>SW (MM)</b>	479	<b>RIM REC</b>	DW 16 L
<b>OD (MM)</b>	1840	<b>RIM ALT</b>	DW 15 L
<b>SLR (MM)</b>	826	<b>ECE</b>	E11-106R-0010410
<b>RC (MM)</b>	5465	<b>SRI</b>	875

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1	1.2	1.4	1.6	2	2.4
<b>70</b>	2395	2755	3160	3570	3975	4385	4790	5095
<b>FROM 65 TO 40</b>	2635	3025	3475	3920	4370	4820	5265	5600
<b>30</b>	2685	3085	3545	4000	4455	4915	5370	5710
<b>20</b>	2740	3145	3610	4075	4540	5010	5475	5820
<b>10</b>	2900	3330	3820	4315	4805	5300	5795	6160
<b>UPTO 30 CYC</b>	2990	3435	3945	4450	4960	5470	5975	6355
<b>UPTO 15 CYC</b>	3565	4100	4705	5310	5920	6525	7130	7585
<b>UPTO 10 CYC</b>	3910	4495	5160	5825	6490	7155	7820	8315
<b>10HT</b>	2685	3085	3545	4000	4455	4915	5370	5710

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.