

# AGRIMAX FORCE

|                  |                                             |
|------------------|---------------------------------------------|
| <b>TIRE SIZE</b> | <b>IF 420/85 R 38</b>                       |
| <b>UM</b>        | IS STANDARD                                 |
| <b>MACHINERY</b> | HARVESTER / HIGH-POWER TRACTOR<br>/ TRACTOR |
| <b>VERSION</b>   | STANDARD                                    |
| <b>TL/TT</b>     | TL                                          |
| <b>LI/SS</b>     | 155 D                                       |



## DIMENSIONS IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 419  | <b>RIM REC</b> | DW 14 L         |
| <b>OD (MM)</b>  | 1670 | <b>RIM ALT</b> | DW 15 L         |
| <b>SLR (MM)</b> | 780  | <b>ECE</b>     | E11-106R-004897 |
| <b>RC (MM)</b>  | 5017 | <b>SRI</b>     | 800             |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR                     | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  | 2.0  | 2.4  |
|--------------------------------|------|------|------|------|------|------|------|------|
| 70                             | 1655 | 1900 | 2180 | 2465 | 2745 | 3030 | 3310 | 3525 |
| FROM 65 TO 40                  | 1820 | 2090 | 2400 | 2710 | 3020 | 3330 | 3640 | 3875 |
| 30                             | 1890 | 2170 | 2495 | 2815 | 3140 | 3460 | 3785 | 4030 |
| 20                             | 1965 | 2255 | 2590 | 2925 | 3260 | 3595 | 3930 | 4185 |
| 10                             | 2310 | 2650 | 3045 | 3440 | 3835 | 4225 | 4620 | 4920 |
| *UPTO 10 CYC WITH FRONT LOADER | 2545 | 2925 | 3360 | 3790 | 4225 | 4660 | 5095 | 5425 |
| 10 HT                          | 1890 | 2170 | 2495 | 2815 | 3140 | 3460 | 3785 | 4030 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.