


# PL 801

<b>TIRE SIZE</b>	<b>21X8 - 9</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	RASTRILLO HILERADOR ROTATIVO / COSECHADORA / CARRETILLA ELEVADORA / COSECHADORA / MAQUINARIA AGRÍCOLA / CARRETILLA ELEVADORA
<b>VERSIÓN</b>	STANDARD
<b>TIRE TYPE</b>	TT



## DIMENSIONES IS STANDARD

<b>SW (MM)</b>	200	<b>ECE</b>	E11-106R-003643
<b>OD (MM)</b>	535	<b>PR</b>	14
<b>RIM REC</b>	6.00 E		
<b>RIM ALT</b>	7.00 E		

## LOAD CAPACITY (KG/TIRE)

<b>KM/H / BAR</b>	<b>9.00</b>
<b>25 LOAD WHEEL</b>	2535
<b>25 STEER WHEEL</b>	1950
<b>10 OTHER VEHICLES</b>	2535
<b>25 OTHER VEHICLES</b>	1950
<b>STATIC SIDE LOADER</b>	2945

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.