


# AT 621

|                           |  |
|---------------------------|--|
| <b>TIRE SIZE</b>          | <b>12.5/80 - 18</b>  |
| <b>UM</b>                 | IS STANDARD  |
| <b>CONSTRUCTION</b>       |  BIAS |
| <b>MACHINERY</b>          | KOMPAKTHJULLASTARE /<br>GRÄVLASTARE / GRÄVLASTARE /<br>HJULLASTARE                     |
| <b>VERSION</b>            | INDUSTRIAL HD  |
| <b>TIRE TYPE</b>          | TL   |
| <b>LI/SS DRIVE WHEEL</b>  | 135 A8   |
| <b>LI/SS FREE ROLLING</b> | 148 A8   |



## DIMENSIONER IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 308  | <b>RIM REC</b> | W 9             |
| <b>OD (MM)</b>  | 987  | <b>RIM ALT</b> | 11.0            |
| <b>SLR (MM)</b> | 434  | <b>ECE</b>     | E11-106R-005365 |
| <b>RC (MM)</b>  | 2916 | <b>PR</b>      | 16              |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 4.90 |
|------------|------|
| 10 FR      | 4410 |
| 25 FR      | 3750 |
| 30 FR      | 3530 |
| 40 FR      | 3150 |
| 10 DW      | 3050 |
| 25 DW      | 2595 |
| 30 DW      | 2440 |
| 40 DW      | 2180 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.