


AGRIMAX V- FLECTO

TIRE SIZE	VF 800/70 R 38
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	HIGH-POWER TRACTOR / TRACTOR
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	187 D



DIMENSIONS IS STANDARD

SW (MM)	804	RIM REC	DW 28 B
OD (MM)	2085	RIM ALT	DW25 B; DW27B; DW30B
SLR (MM)	890	ECE	E11-106R-0011027
RC (MM)	6155	SRI	975

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0
70	4440	5150	5860	6660	7370	8080	8875
FROM 65 TO 40	4875	5655	6435	7315	8095	8875	9750
30	4975	5770	6565	7460	8255	9050	9945
20	5070	5885	6695	7605	8420	9230	10140
10	5365	6225	7080	8045	8905	9760	10725
10 HT	4975	5770	6565	7460	8255	9050	9945
UPTO 10 CYC WITH FRONT LOADER	6825	7920	9010	10240	11330	12425	13650

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.