


# RIDEMAX IT 696

|                     |  |
|---------------------|--|
| <b>TYRE SIZE</b>    | <b>540/80 R 38 IND</b>   |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | TRACTOR  |
| <b>VERSION</b>      | STANDARD   |
| <b>TL/TT</b>        | TL   |
| <b>LI/SS</b>        | 172 A8 ; 167 D   |



## DIMENSIONS IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 550  | <b>RIM REC</b> | W 18 L          |
| <b>OD (MM)</b>  | 1829 | <b>RIM ALT</b> | W 16 L          |
| <b>SLR (MM)</b> | 833  | <b>ECE</b>     | E11-106R-004077 |
| <b>RC (MM)</b>  | 5537 | <b>SRI</b>     | 875             |

## LOAD CAPACITY (KG/TYRE)

| KM/H / BAR | 0.6  | 0.8  | 1    | 1.2  | 1.4  | 1.6  |
|------------|------|------|------|------|------|------|
| 65         | 1075 | 1250 | 1425 | 1600 | 1775 | 1950 |
| 50         | 1130 | 1315 | 1500 | 1685 | 1870 | 2050 |
| 40         | 1180 | 1370 | 1565 | 1755 | 1950 | 2140 |
| 30         | 1235 | 1440 | 1640 | 1845 | 2045 | 2245 |
| 10 LT      | 1440 | 1675 | 1910 | 2145 | 2380 | 2615 |
| 10HT       | 1235 | 1440 | 1640 | 1845 | 2045 | 2245 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.