

# AGRIMAX TURF RT 333

<b>TIRE SIZE</b>	<b>280/70 R 16</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / МАШИНА ДЛЯ СБОРА ФРУКТОВ / МИНИ- ТРАКТОР / ТРАКТОР-ТЯГАЧ / КОМБАЙН
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	112 A8 ; 112 B



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94065714	<b>RC (IN)</b>	93.3
<b>SW (IN)</b>	11.4	<b>RIM REC</b>	W9
<b>OD (IN)</b>	31.5	<b>RIM ALT</b>	W 8; W 10
<b>SLR (IN)</b>	14.1	<b>ECE</b>	E11-106R-006472

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
30	1170	1330	1530	1730	1930	2130	2330	2470
25	1170	1330	1530	1730	1930	2130	2330	2470
20	1250	1430	1640	1850	2070	2280	2490	2650
5 LT	1570	1800	2060	2330	2590	2850	3120	3320
5 HT	1250	1430	1640	1850	2070	2280	2490	2650

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.