


# AGRIMAX V- FLECTO

<b>TIRE SIZE</b>	<b>VF 520/70 R 38</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRATTORE / TRATTORE A ELEVATA POTENZA
<b>VERSIONE</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	164 D



## DIMENSIONI IS STANDARD

<b>SW (MM)</b>	536	<b>RIM REC</b>	DW 18 L
<b>OD (MM)</b>	1750	<b>ECE</b>	E11-106R-0011692
<b>SLR (MM)</b>	773	<b>SRI</b>	825
<b>RC (MM)</b>	5213	<b>TRA CODE</b>	R1W

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1	1.2	1.4	1.6	2
70	2275	2640	3005	3415	3780	4145	4550
FROM 65 TO 40	2500	2900	3300	3750	4150	4550	5000
30	2550	2960	3370	3825	4235	4645	5100
20	2600	3020	3435	3900	4320	4735	5200
10	2750	3190	3630	4125	4565	5005	5500
10HT	2550	2958	3366	3825	4233	4641	5100
UPTO 10 CYC WITH FRONT LOADER	3500	4060	4620	5250	5810	6370	7000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.