


# MULTIMAX MP 522



|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>400/80 R 24 IND</b>   |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | COMPACT LOADER / TELEHANDLER /<br>COMPACT LOADER / TELEHANDLER                           |
| <b>VERSION</b>      | STANDARD   |
| <b>TL/TT</b>        | TL   |
| <b>LI/SS</b>        | 162 A8/B   |

## DIMENSIONS IS STANDARD

|                 |      |                |                           |
|-----------------|------|----------------|---------------------------|
| <b>SW (MM)</b>  | 404  | <b>RIM REC</b> | DW 13                     |
| <b>OD (MM)</b>  | 1250 | <b>RIM ALT</b> | DW 12 ; DW 13 L ; DW 14 L |
| <b>SLR (MM)</b> | 565  | <b>ECE</b>     | E11-106R-002965           |
| <b>RC (MM)</b>  | 3787 | <b>SRI</b>     | 600                       |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.6  | 2.0  | 2.4  | 2.8  | 3.2  | 3.4  | 3.6  | 4.0  | 4.4  | 4.6  | 4.8  | 5.0   | 5.2   | 5.4   |
|------------|------|------|------|------|------|------|------|------|------|------|------|-------|-------|-------|
| 50         | 1855 | 2185 | 2565 | 2900 | 3230 | 3350 | 3520 | 3895 | 4220 | 4435 | 4540 | 4750  | -     | -     |
| 40         | 1855 | 2185 | 2565 | 2900 | 3230 | 3350 | 3520 | 3895 | 4220 | 4435 | 4540 | 4750  | -     | -     |
| 30         | 1985 | 2340 | 2750 | 3105 | 3460 | 3590 | 3770 | 4170 | 4515 | 4745 | 4860 | 5085  | -     | -     |
| 25         | 2060 | 2430 | 2850 | 3220 | 3590 | 3725 | 3910 | 4330 | 4690 | 4925 | 5040 | 5275  | -     | -     |
| 10 CYC.    | 2280 | 2785 | 3280 | 3850 | 4350 | 4600 | 4845 | 5280 | 5845 | 6090 | 6330 | 6655  | 6810  | 7125  |
| STATIC     | 3500 | 4270 | 5030 | 5900 | 6670 | 7050 | 7430 | 8100 | 8960 | 9340 | 9710 | 10205 | 10445 | 10925 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.