

AW 702

| | |
|---------------------------|---|
| TIRE SIZE | 10.0/80 - 12 |
| UM | US STANDARD |
| CONSTRUCTION | ⊠ BIAS |
| MACHINERY | EMPACADORA DE HENO / MAQUINARIA AGRÍCOLA / REMOLQUE / COSECHADORA / MAQUINARIA AGRÍCOLA / REMOLQUE |
| VERSIÓN | SPECIAL |
| TIRE TYPE | TL |
| LI/SS FREE ROLLING | 121 A8 |



DIMENSIONES US STANDARD

| | | | |
|-------------------|----------|----------------|-----------------|
| CÓDIGO USA | 94040001 | RC (IN) | 84.4 |
| SW (IN) | 10.4 | RIM REC | 9.00 |
| OD (IN) | 28.0 | RIM ALT | 7.0 |
| SLR (IN) | 12.5 | ECE | E11-106R-004353 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 57 |
|-----------|------|
| 5 FR | 4480 |
| 15 FR | 3800 |
| 20 FR | 3580 |
| 25 FR | 3200 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.