

AGRIMAX V-FLECTO

TYRE SIZE	VF 620/70 R 42
UM	US STANDARD
MACHINERY	HIGH-POWER TRACTOR / TRACTOR
VERSION	STANDARD
TL/TT	TL
LI/SS	175 D



DIMENSIONS US STANDARD

USA CODE	94514205	RIM REC	DW 21 B
SW (IN)	24.4	RIM ALT	DW 20 B ; DW 23 B
OD (IN)	76.2	ECE	E11-106R-0011233
SLR (IN)	33.4	TREAD DEPTH (32nd)	73.08
RC (IN)	228.1	TMPH (TM/H)	0

LOAD CAPACITY (LBS/TYRE)

MPH / PSI	9	12	15	17	20	23	29
45	6920	8020	9140	10380	11490	12600	13830
FROM 40 TO 25	7610	8830	10040	11410	12630	13840	15210
20	7760	9010	10240	11640	12870	14120	15510
12	7910	9180	10450	11870	13140	14400	15820
5	8370	9710	11040	12550	13890	15230	16730
*UPTO 5 CYC WITH FRONT LOADER	10650	12360	14060	15970	17680	19390	21300
5 HT	7760	9010	10240	11640	12870	14120	15510

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.