


# POWERTRAILER SR 331

|              |  |
|--------------|--|
| TIRE SIZE    | 560/60 R 22.5  |
| UM           | US STANDARD  |
| CONSTRUCTION |  RADIAL |
| MACHINERY    | REMOLQUE / MAQUINARIA AGRÍCOLA<br>/ CAMIÓN CISTERNA                                      |
| VERSIÓN      | IMPLEMENT  |
| TIRE TYPE    | TL   |
| LI/SS        | 165 D  |



## DIMENSIONES US STANDARD

|            |          |         |                  |
|------------|----------|---------|------------------|
| CÓDIGO USA | 94073962 | RIM REC | AG 16.00         |
| OD (IN)    | 49.0     | RIM ALT | 17.00; AG18.00   |
| SLR (IN)   | 22.2     | ECE     | E11-106R-0010087 |
| RC (IN)    | 148.6    |         |                  |

## LOAD CAPACITY (LBS/TIRE)

| MPH/PSI | 46    | 52    | 58    | 65    | 73    |
|---------|-------|-------|-------|-------|-------|
| 5       | 15120 | 16550 | 18200 | 19420 | 20440 |
| 15      | 13270 | 14530 | 15970 | 17050 | 17930 |
| 25      | 11420 | 12500 | 13750 | 14670 | 15440 |
| 30      | 10160 | 11120 | 12240 | 13060 | 13730 |
| 40      | 8400  | 9190  | 10110 | 10790 | 11350 |
| 43      | 7640  | 8370  | 9190  | 9820  | 10330 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.