

AS 504

| | |
|---------------------------|--|
| TIRE SIZE | 11.5/80 - 15.3 |
| UM | US STANDARD |
| CONSTRUCTION | ⊠ BIAS |
| MACHINERY | ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК |
| VERSION | STANDARD |
| TIRE TYPE | TT |
| LI/SS DRIVE WHEEL | 114 A8 |
| LI/SS FREE ROLLING | 126 A8 |



РАЗМЕРЫ US STANDARD

| | | | |
|-----------------|----------|----------------|----------------|
| USA CODE | 94018666 | RC (IN) | 100.0 |
| SW (IN) | 11.4 | RIM REC | 9.00 |
| OD (IN) | 34.1 | ECE | E4-106R-001892 |
| SLR (IN) | 15.0 | PR | 8 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 39 |
|-----------|------|
| 5 FR | 5250 |
| 15 FR | 4460 |
| 20 FR | 4200 |
| 25 FR | 3750 |
| 5 DW | 3640 |
| 15 DW | 3100 |
| 20 DW | 2910 |
| 25 DW | 2600 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.