

MAGLIFT



MAGLIFT
S O L I D T I R E S

MAGLIFT



MAGLIFT has been particularly designed for forklift in industrial and logistic operations. This solid tire features high load capacity and outstanding comfort. MAGLIFT shows excellent cut and chip resistance resulting in a long tire life. Its reinforced structure eliminates slippage risks whilst the special bead shape simplifies mounting operations on the rim.



SIZE	TT/TL	STAR RATING	LI/SS	RIM		O.W. (mm)	OD (mm)	SLR (mm)	RC (mm)	VERSION
				REC RIM	ALT RIM					
										
Ø8"	18X7 -8 (180/70 - 8)	-	-				457	0	0	STD
	15X4.5 -8 (125/75 - 8)	-	-				378	0	0	LIP - NM
	15X4.5 -8 (125/75 - 8)	-	-	-	-		378	0	0	STD
	16X6 -8 (150/75 - 8)	-	-		-		421	0	0	LIP
	5.00 - 8	-	-	-	-		462	0	0	STD

LIP: LIP, STD: STANDARD, LIP - NM: LIP - NON MARKING, STD - NM: STANDARD - NON MARKING

TECHNOLOGIES		PERFORMANCES	
			
			
-	-	Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index	

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US – 15/07/2026

SIZE	TT/TL	STAR RATING	LI/SS	RIM		O.W. (mm)	OD (mm)	SLR (mm)	RC (mm)	VERSION
				REC RIM	ALT RIM					
										
5.00 - 8	-	-	-	3.00 D - 8	-		462	0	0	LIP
5.00 - 8	-	-	-	3.00 D - 8	-		462	0	0	LIP - NM
15X4.5 - 8 (125/75 - 8)	-	-		3.00 D - 8	-		378	0	0	LIP
18X7 - 8 (180/70 - 8)	-	-		4.33 R - 8	-		457	0	0	LIP - NM
4.00 - 8	-	-	-	3.00 D - 8	-		406	0	0	LIP
16X6 - 8 (150/75 - 8)	-	-		4.33 R - 8	-		421	0	0	LIP - NM
4.00 - 8	-	-	-	3.00 D - 8	-		406	0	0	LIP - NM
18X7 - 8 (180/70 - 8)	-	-		4.33 R - 8	-		457	0	0	LIP
5.00 - 8	-	-	-	3.00 D - 8	-		462	0	0	STD - NM
16X6 - 8 (150/75 - 8)	-	-		4.33 R - 8	-		421	0	0	STD

LIP: LIP, STD: STANDARD, LIP - NM: LIP - NON MARKING, STD - NM: STANDARD - NON MARKING

TECHNOLOGIES		PERFORMANCES	
			
			
-	-		

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US – 15/07/2026

SIZE	TT/TL	STAR RATING	LI/SS	RIM		O.W. (mm)	OD (mm)	SLR (mm)	RC (mm)	VERSION
				REC RIM	ALT RIM					
										
16X6 -8 (150/75 - 8)	-	-		4.33 R - 8	-		421	0	0	STD - NM
4.00 - 8	-	-	-	3.00 D - 8	-		406	0	0	STD
4.00 - 8	-	-	-	3.00 D - 8	-		406	0	0	STD - NM
15X4.5 -8 (125/75 - 8)	-	-		3.00 D - 8	-		378	0	0	STD - NM
18X7 -8 (180/70 - 8)	-	-		4.33 R - 8	-		457	0	0	STD - NM
	6.00 - 9	-	-	4.00 E - 9	-		529	0	0	LIP - NM
	140/55 - 9	-	-	4.00 E - 9	-		377	0	0	STD - NM
	21X8 -9 (200/75 - 9)	-	-	6.00 E - 9	-		525	0	0	STD
	140/55 - 9	-	-	4.00 E - 9	-		377	0	0	STD
	21X8 -9 (200/75 - 9)	-	-	6.00 E - 9	-		525	0	0	LIP - NM

LIP: LIP, STD: STANDARD, LIP - NM: LIP - NON MARKING, STD - NM: STANDARD - NON MARKING

TECHNOLOGIES		PERFORMANCES	
			
			
-	-		

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US – 15/07/2026

SIZE	TT/TL	STAR RATING	LI/SS	RIM		O.W. (mm)	OD (mm)	SLR (mm)	RC (mm)	VERSION
				REC RIM	ALT RIM					
										
140/55 - 9	-	-	-	4,00 E - 9	-		377	0	0	LIP - NM
21X8 - 9 (200/75 - 9)	-	-		6,00 E - 9	-		525	0	0	STD - NM
6.00 - 9	-	-	-	4,00 E - 9	-		529	0	0	LIP
21X8 - 9 (200/75 - 9)	-	-		6,00 E - 9	-		525	0	0	LIP
6.00 - 9	-	-	-	4,00 E - 9	-		529	0	0	STD - NM
140/55 - 9	-	-	-	4,00 E - 9	-		377	0	0	LIP
6.00 - 9	-	-	-	4,00 E - 9	-		529	0	0	STD
Ø10"	6.50 - 10	-	-	5,00 F - 10	-		575	0	0	LIP - NM
	6.50 - 10	-	-	5,00 F - 10	-		575	0	0	STD
	200/50 - 10	-	-	6,50 F - 10	-		458	0	0	LIP - NM

LIP: LIP, STD: STANDARD, LIP - NM: LIP - NON MARKING, STD - NM: STANDARD - NON MARKING

TECHNOLOGIES		PERFORMANCES	
			
			
-	-		

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US – 15/07/2026

SIZE	TT/TL	STAR RATING	LI/SS	RIM		O.W. (mm)	OD (mm)	SLR (mm)	RC (mm)	VERSION
				REC RIM	ALT RIM					
										
200/50 - 10	-	-	-	6.50 F - 10	-		458	0	0	STD
180/60 - 10	-	-	-	5.00F-10	-		460	0	0	LIP
200/50 - 10	-	-	-	6.50 F - 10	-		458	0	0	LIP
180/60 - 10	-	-	-	5.00F-10	-		460	0	0	STD
200/50 - 10	-	-	-	6.50 F - 10	-		458	0	0	STD - NM
6.50 - 10	-	-	-	5.00 F - 10	-		575	0	0	LIP
23X9 -10 (225/75 - 10)	-	-		6.50 F - 10	-		585	0	0	STD - NM
23X9 -10 (225/75 - 10)	-	-		6.50 F - 10	-		585	0	0	LIP - NM
23X9 -10 (225/75 - 10)	-	-		6.50 F - 10	-		585	0	0	LIP
23X9 -10 (225/75 - 10)	-	-		6.50 F - 10	-		585	0	0	STD

LIP: LIP, STD: STANDARD, LIP - NM: LIP - NON MARKING, STD - NM: STANDARD - NON MARKING

TECHNOLOGIES		PERFORMANCES	
			
			
-	-		

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US – 15/07/2026

	SIZE	TT/TL	STAR RATING	LI/SS	RIM		O.W. (mm)	OD (mm)	SLR (mm)	RC (mm)	VERSION
					REC RIM	ALT RIM					
											
	6.50 - 10	-	-	-	5.00 F - 10	-		575	0	0	STD - NM
Ø12"	7.00 - 12	-	-	-	5.00 S - 12	-		658	0	0	LIP
	27X10 - 12 (250/75 - 12)	-	-		8.00 G - 12	-		677	0	0	LIP - NM
	7.00 - 12	-	-	-	5.00 S - 12	-		658	0	0	STD
	27X10 - 12 (250/75 - 12)	-	-		8.00 G - 12	-		677	0	0	LIP
	315/45 - 12	-	-	-	10.00G-12	-		578	0	0	STD
	27X10 - 12 (250/75 - 12)	-	-		8.00 G - 12	-		677	0	0	STD
	315/45 - 12	-	-	-	10.00G-12	-		578	0	0	LIP
	23X10 - 12 (250/60 - 12)	-	-		8.00 G - 12	-		584	0	0	LIP - NM
	7.00 - 12	-	-	-	5.00 S - 12	-		658	0	0	LIP - NM

LIP: LIP, STD: STANDARD, LIP - NM: LIP - NON MARKING, STD - NM: STANDARD - NON MARKING

TECHNOLOGIES		PERFORMANCES	
			
			
-	-		

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US – 15/07/2026

SIZE	TT/TL	STAR RATING	LI/SS	RIM		O.W. (mm)	OD (mm)	SLR (mm)	RC (mm)	VERSION
				REC RIM	ALT RIM					
										
23X10 - 12 (250/60 - 12)	-	-		8.00 G - 12	-		584	0	0	LIP
7.00 - 12	-	-	-	5.00 S - 12	-		658	0	0	STD - NM
27X10 - 12 (250/75 - 12)	-	-		8.00 G - 12	-		677	0	0	STD - NM
23X10 - 12 (250/60 - 12)	-	-		8.00 G - 12	-		584	0	0	STD - NM
23X10 - 12 (250/60 - 12)	-	-		8.00 G - 12	-		584	0	0	STD
Ø15"	300 - 15 (315/70 - 15)	-	-	8.0 - 15	-		820	0	0	LIP
	7.50 - 15	-	-	5.5 - 15	-		756	0	0	LIP
	7.00 - 15	-	-	5.5 - 15	-		730	0	0	LIP
	7.50 - 15	-	-	5.5 - 15	-		756	0	0	STD - NM
	300 - 15 (315/70 - 15)	-	-	8.0 - 15	-		820	0	0	LIP - NM

LIP: LIP, STD: STANDARD, LIP - NM: LIP - NON MARKING, STD - NM: STANDARD - NON MARKING

TECHNOLOGIES		PERFORMANCES	
			
			
-	-	Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index	

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US – 15/07/2026

SIZE	TT/TL	STAR RATING	LI/SS	RIM		O.W. (mm)	OD (mm)	SLR (mm)	RC (mm)	VERSION
				REC RIM	ALT RIM					
										
7.00 - 15	-	-		5.5 - 15	-		730	0	0	STD
7.50 - 15	-	-	-	6.0 - 15	-		756	0	0	LIP - NM
28X12.5 - 15 (355/45 - 15)	-	-		9.75 - 15	-		687	0	0	STD
28X12.5 - 15 (355/45 - 15)	-	-		9.75 - 15	-		687	0	0	STD - NM
300 - 15 (315/70 - 15)	-	-	-	8.0 - 15	-		820	0	0	STD - NM
7.50 - 15	-	-	-	6.0 - 15	-		756	0	0	LIP
250 - 15 (250/70 - 15)	-	-	-	7.0 - 15	-		718	0	0	LIP - NM
250 - 15 (250/70 - 15)	-	-	-	7.0 - 15	-		718	0	0	LIP
8.25 - 15	-	-	-	6.5 - 15	-		818	0	0	LIP
8.25 - 15	-	-	-	6.5 - 15	-		818	0	0	STD

LIP: LIP, STD: STANDARD, LIP - NM: LIP - NON MARKING, STD - NM: STANDARD - NON MARKING

TECHNOLOGIES		PERFORMANCES	
			
			
-	-		

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US – 15/07/2026

SIZE	TT/TL	STAR RATING	LI/SS	RIM		O.W. (mm)	OD (mm)	SLR (mm)	RC (mm)	VERSION
				REC RIM	ALT RIM					
										
32X12.5 - 15 (355 / 65 - 15)	-	-		9.75 - 15	-		825			LIP
8.15 - 15 (28X9-15; 225/75-15)	-	-		7.0 - 15	-		691	0	0	STD - NM
250 - 15 (250/70 - 15)	-	-	-	7.0 - 15	-		718	0	0	STD - NM
7.50 - 15	-	-	-	5.5 - 15	-		756	0	0	STD
5.50 - 15	-	-	-	4.50 E - 15	-		665			STD
28X12.5 - 15 (355/45 - 15)	-	-		9.75 - 15	-		687	0	0	LIP
8.15 - 15 (28X9-15; 225/75-15)	-	-		7.0 - 15	-		691	0	0	LIP
28X12.5 - 15 (355/45 - 15)	-	-		9.75 - 15	-		687	0	0	LIP - NM
300 - 15 (315/70 - 15)	-	-	-	8.0 - 15	-		820	0	0	STD
8.15 - 15 (28X9-15; 225/75-15)	-	-		7.0 - 15	-		691	0	0	LIP - NM

LIP: LIP, STD: STANDARD, LIP - NM: LIP - NON MARKING, STD - NM: STANDARD - NON MARKING

TECHNOLOGIES		PERFORMANCES	
			
			
-	-		

Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US – 15/07/2026

SIZE	TT/TL	STAR RATING	LI/SS	RIM		O.W. (mm)	OD (mm)	SLR (mm)	RC (mm)	VERSION
				REC RIM	ALT RIM					
										
7.50 - 15	-	-	-	6.0 - 15	-		756	0	0	STD - NM
7.00 - 15	-	-		5.5 - 15	-		730	0	0	STD - NM
8.25 - 15	-	-	-	6.5 - 15	-		818	0	0	LIP - NM
32X12.5 - 15 (355 / 65 - 15)	-	-		9.75 - 15	-		825			STD
8.15 - 15 (28X9-15; 225/75-15)	-	-		7.0 - 15	-		691	0	0	STD
7.00 - 15	-	-		5.5 - 15	-		730	0	0	LIP - NM
7.50 - 15	-	-	-	5.5 - 15	-		756	0	0	LIP - NM
7.50 - 15	-	-	-	6.0 - 15	-		756	0	0	STD
8.25 - 15	-	-	-	6.5 - 15	-		818	0	0	STD - NM
250 - 15 (250/70 - 15)	-	-	-	7.0 - 15	-		718	0	0	STD

LIP: LIP, STD: STANDARD, LIP - NM: LIP - NON MARKING, STD - NM: STANDARD - NON MARKING

TECHNOLOGIES		PERFORMANCES	
			
			
-	-		

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US – 15/07/2026

	SIZE	TT/TL	STAR RATING	LI/SS	RIM		O.W. (mm)	OD (mm)	SLR (mm)	RC (mm)	VERSION
					REC RIM	ALT RIM					
											
NEW	355/50 - 15	-	-		9.75 - 15	-		721	0	0	STD
	355/50 - 15	-	-		9.75 - 15	-		721	0	0	LIP
Ø20"	12.00 - 20	-	-	-	8.50 - 20	-		1090			STD
	10.00 - 20	-	-	-	7.50 - 20	-		1035			STD
	10.00 - 20	-	-	-	8.00 - 20	-		1035			STD
	10.00 - 20	-	-	-	7.00 - 20	-		1035			STD
	11.00 - 20	-	-	-	8.00 - 20	-		1060			STD
	9.00 - 20	-	-	-	7.00 - 20	-		990			STD
	12.00 - 20	-	-	-	8.00 - 20	-		1090			STD
	9.00 - 20	-	-	-	6.50 - 20	-		990			STD

LIP: LIP, STD: STANDARD, LIP - NM: LIP - NON MARKING, STD - NM: STANDARD - NON MARKING

TECHNOLOGIES		PERFORMANCES	
			
			
-	-		

Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US – 15/07/2026

	SIZE	TT/TL	STAR RATING	LI/SS	RIM		O.W. (mm)	OD (mm)	SLR (mm)	RC (mm)	VERSION
					REC RIM	ALT RIM					
											
	11.00 - 20	-	-	-	7.50 - 20	-		1060			STD
Ø24"	14.00 - 24	-	-	-	10.00 - 24	-		1320			STD

LIP: LIP, STD: STANDARD, LIP - NM: LIP - NON MARKING, STD - NM: STANDARD - NON MARKING

TECHNOLOGIES		PERFORMANCES	
			
			
-	-		

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US – 15/07/2026