

# SKID POWER (CHEVRON)

|                     |             |
|---------------------|-------------|
| <b>TIRE SIZE</b>    | 7.00 - 15   |
| <b>UM</b>           | IS STANDARD |
| <b>CONSTRUCTION</b> |             |
| <b>MACHINERY</b>    | SKID STEER  |
| <b>VERSION</b>      | IMPLEMENT   |
| <b>TL/TT</b>        | TL          |
| <b>LI/SS</b>        | 106 A8      |



## DIMENSIONS IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 203  | <b>RIM REC</b> | 5.50 F          |
| <b>OD (MM)</b>  | 762  | <b>RIM ALT</b> | 6 LB            |
| <b>SLR (MM)</b> | 347  | <b>ECE</b>     | E11-106R-003583 |
| <b>RC (MM)</b>  | 2295 | <b>PR</b>      | 6               |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>4.10</b> |
| 40                | 950         |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.