


# AGRIMAX V-FLECTO



<b>TIRE SIZE</b>	<b>VF 650/60 R 38</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	MOTORSTARK TRAKTOR / TRAKTOR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	173 D

## DIMENSIONER US STANDARD

<b>USA CODE</b>	94065370	<b>RC (IN)</b>	205.4
<b>SW (IN)</b>	25.6	<b>RIM REC</b>	DW 23 B
<b>OD (IN)</b>	68.7	<b>RIM ALT</b>	DW 21 B
<b>SLR (IN)</b>	30.5	<b>ECE</b>	E11-106R-006415

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
45	6010	6910	7960	8870	9920	10820	12140	13040
<b>FROM 40 TO 25</b>	6590	7590	8740	9740	10890	11890	13330	14330
20	6720	7750	8920	9940	11110	12140	13600	14620
12	6860	7900	9090	10140	11330	12380	13870	14900
5	7250	8360	9620	10720	11980	13080	14660	15760
<b>*UPTO 5 CYC WITH FRONT LOADER</b>	9240	10640	12250	13650	15260	16650	18660	20060
5 HT	6720	7750	8920	9940	11110	12140	13600	14620

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.