

# CON STAR

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | 340/80 - 20  |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> | ❖ BIAS   |
| <b>MACHINERY</b>    | KOMPAKTLADER / TELESKOPLADER /<br>KOMPAKTLADER / TELESKOPLADER |
| <b>VERSION</b>      | INDUSTRIAL   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 144 A8   |



## ABMESSUNGEN US STANDARD

|                 |          |                |                                |
|-----------------|----------|----------------|--------------------------------|
| <b>USA-CODE</b> | 94051311 | <b>RC (IN)</b> | 128.8                          |
| <b>SW (IN)</b>  | 13.8     | <b>RIM REC</b> | 11                             |
| <b>OD (IN)</b>  | 41.9     | <b>RIM ALT</b> | 12; 11 SDC; 12 SDC; W 10; W 11 |
| <b>SLR (IN)</b> | 19.3     | <b>ECE</b>     | E11-106R-003021                |

## LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>58</b> |
| 25               | 6170      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.