

AGRIMAX RT 765

TIRE SIZE	420/70 R 30
UM	IS STANDARD
MACHINERY	FELDSPRITZE / TRACTOR / TRAUBENERNTEMASCHINE / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	134 D



ABMESSUNGEN IS STANDARD

SW (MM)	418	RIM ALT	W 12 ; W 14 L
OD (MM)	1398	ECE	E11-106R-005830
SLR (MM)	631	SRI	675
RC (MM)	4172	TRA CODE	R1W
RIM REC	W 13	TREAD DEPTH (MM)	43,5

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
65	1170	1360	1550	1740	1930	2120
50	1230	1430	1630	1830	2030	2230
40	1280	1490	1700	1910	2120	2325
30	1345	1565	1785	2005	2225	2440
10 LT	1565	1825	2080	2335	2590	2845
10 HT	1345	1565	1785	2005	2225	2440

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.