


# AGRIMAX RT 765

<b>TYRE SIZE</b>	<b>710/70 R 38</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTOR / IMPLEMENTS
<b>VERSION</b>	SPECIAL
<b>TL/TT</b>	TL
<b>LI/SS</b>	175 D ; 178 A8



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	716	<b>RIM REC</b>	DW 23 B
<b>OD (MM)</b>	1959	<b>ECE</b>	E11-106R-006000
<b>SLR (MM)</b>	859	<b>SRI</b>	925
<b>RC (MM)</b>	5751	<b>TRA CODE</b>	R1W

## LOAD CAPACITY (KG/TYRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2
65	2695	3175	3660	4075	4555	4970	5455	5865	6420	6900
50	2830	3335	3840	4275	4785	5220	5725	6160	6740	7245
40	2925	3450	3975	4425	4950	5400	5925	6375	6975	7500
30	3095	365	4210	4685	5240	5715	6270	6745	7380	7935
10 LT	3610	4255	4905	5460	6105	6660	7310	7865	8605	9250
10 HT	3095	3655	4210	4685	5240	5715	6270	6745	7380	7935

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.