

RIDEMAX FROST

TIRE SIZE	440/80 R 24 IND
UM	US STANDARD
CONSTRUCTION	
MACHINERY	TRACTOR
VERSION	STEEL BELTED
TL/TT	TL
LI/SS	154 A8 ; 149 D



DIMENSIONS US STANDARD

USA CODE	94517084	RC (IN)	156.9
SW (IN)	17.4	RIM REC	DW 14 L
OD (IN)	51.7	RIM ALT	DW 15 L
SLR (IN)	23.5	ECE	E11-106R-0011765

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	17	23	29	35	38	41	44	46
45	3300	4230	5160	5670	6100	6380	6670	6960	7160
30	3560	4570	5580	6120	6580	6890	7200	7510	7740
25	3800	4870	5940	6510	7010	7340	7670	8000	8270
20	3960	5080	6190	6800	7310	7660	8000	8340	8600
10	4160	5330	6500	7140	7680	8040	8400	8760	9030
5	4750	6100	7430	8160	8770	9190	9600	10010	10320
3	5510	7070	8620	9460	10180	10660	11130	11620	11970

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.