


# AGRIMAXFACTOR

|                     |  |
|---------------------|--|
| <b>TYRE SIZE</b>    | <b>480/70 R 30</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | TRACTOR  |
| <b>VERSION</b>      | STANDARD   |
| <b>TL/TT</b>        | TL   |
| <b>LI/SS</b>        | 141 D ; 144 A8   |



## DIMENSIONS US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94074792 | <b>RC (IN)</b> | 172.9           |
| <b>SW (IN)</b>  | 18.9     | <b>RIM REC</b> | W 15 L          |
| <b>OD (IN)</b>  | 58.2     | <b>RIM ALT</b> | W 14 L ; W 16 L |
| <b>SLR (IN)</b> | 26.4     | <b>ECE</b>     | E11-106R-008811 |

## LOAD CAPACITY (LBS/TYRE)

| MPH / PSI | 9    | 12   | 15   | 17   | 20   | 23   |
|-----------|------|------|------|------|------|------|
| 40        | 3130 | 3640 | 4140 | 4660 | 5170 | 5680 |
| 30        | 3280 | 3820 | 4350 | 4890 | 5430 | 5960 |
| 25        | 3430 | 3980 | 4540 | 5100 | 5670 | 6150 |
| 20        | 3600 | 4190 | 4770 | 5370 | 5950 | 6540 |
| 5 LT      | 4200 | 4880 | 5570 | 6250 | 6930 | 7620 |
| 5 HT      | 3600 | 4190 | 4770 | 5370 | 5950 | 6540 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.