DATA SHEET

PRINTED ON
23-04-2026

EARTHMAX SR 43

TIRE SIZE	**875/65 R 29**
UM	US STANDARD
CONSTRUCTION	RADIAL
MACHINERY	HJULLASTARE
VERSION	CUT RESISTANT COMPOUND
TIRE TYPE	TL
LI/SS	228 A2

DIMENSIONER US STANDARD

USA CODE	94071098	**RIM REC**	27.00/3.5
OD (IN)	73.9	**RIM ALT**	27.00/3.0; 28.00/3.5
SLR (IN)	33.2	**TRA CODE**	L4
RC (IN)	224.5	**STAR RATING**	★★★

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	94	98	102	105	109	112	116
5	58400	60000	61500	64000	66000	68000	69500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..