

TR 882

TIRE SIZE	400/60 - 15.5
UM	IS STANDARD
CONSTRUCTION	BIAS
MACHINERY	ПРЕСС-ПОДБОРЩИК / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ПРИЦЕП / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ПРИЦЕП
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	122 A8
LI/SS FREE ROLLING	134 A8



РАЗМЕРЫ IS STANDARD

SW (MM)	400	RIM REC	AG 13.00
OD (MM)	875	ECE	E11-106R-004330
SLR (MM)	378	PR	8
RC (MM)	2605	SRI	410

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	2.40
10 FR	2970
25 FR	2525
30 FR	2375
40 FR	2120
10 DW	2100
25 DW	1785
30 DW	1680
40 DW	1500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.