

AGRIMAX RT 765

TIRE SIZE	420/70 R 24
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ОПРЫСКИВАТЕЛЬ / ТРАКТОР-ТЯГАЧ / КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
VERSION	SPECIAL
TIRE TYPE	TL
LI/SS	130 D



РАЗМЕРЫ IS STANDARD

SW (MM)	418	RIM REC	W 13
OD (MM)	1248	RIM ALT	W 12; W 14 L
SLR (MM)	554	ECE	E11-106R-005826
RC (MM)	3680	SRI	600

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
65	1045	1220	1390	1560	1730	1900
50	1100	1280	1460	1640	1820	1995
40	1150	1335	1525	1710	1900	2085
30	1205	1400	1600	1795	1990	2185
10 LT	1405	1635	1865	2095	2325	2550
10 HT	1205	1400	1600	1795	1990	2185

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.