


AGRIMAX RT 765

| | |
|---------------------|--|
| | 480/70 R 30 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | ILAÇLAMA / TRAKTÖR / ÜZÜM HASAT MAKINESİ / BIÇERDÖVER / UYGULAMALI MAKİNE |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| | 141 D |



UNDEFINED US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------|
| USA CODE | 94062218 | RC (IN) | 172.1 |
| SW (IN) | 18.9 | RIM REC | W 15 L |
| OD (IN) | 58.2 | RIM ALT | W 14 L; W 16 L |
| SLR (IN) | 25.9 | ECE | E11-106R-005522 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 |
|-----------|------|------|------|------|------|------|
| 40 | 3130 | 3640 | 4140 | 4660 | 5170 | 5680 |
| 30 | 3280 | 3820 | 4350 | 4890 | 5430 | 5960 |
| 25 | 3430 | 3980 | 4540 | 5100 | 5670 | 6220 |
| 20 | 3600 | 4190 | 4770 | 5370 | 5950 | 6540 |
| 5 LT | 4200 | 4880 | 5570 | 6250 | 6930 | 7620 |
| 5 HT | 3600 | 4190 | 4770 | 5370 | 5950 | 6540 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.