

# SKID POWER HD (A)

|                     |                      |
|---------------------|----------------------|
| <b>TIRE SIZE</b>    | <b>31X15.5 - 15</b>  |
| <b>UM</b>           | US STANDARD          |
| <b>CONSTRUCTION</b> | ⊠ BIAS               |
| <b>MACHINERY</b>    | КОМПАКТНЫЙ ПОГРУЗЧИК |
| <b>VERSION</b>      | IMPLEMENT            |
| <b>TIRE TYPE</b>    | TL                   |
| <b>LI/SS</b>        | 125 A8               |



## РАЗМЕРЫ US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94056057 | <b>RC (IN)</b> | 94.9            |
| <b>SW (IN)</b>  | 15.9     | <b>RIM REC</b> | 13 LB           |
| <b>OD (IN)</b>  | 31.1     | <b>ECE</b>     | E11-106R-003375 |
| <b>SLR (IN)</b> | 14.9     | <b>PR</b>      | 10              |

## LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>61</b> |
| 25               | 3640      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.