

AS 504

TIRE SIZE	10.0/80 - 12
UM	US STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	109 A8
LI/SS FREE ROLLING	121 A8



РАЗМЕРЫ US STANDARD

USA CODE	94063963	RC (IN)	87.9
SW (IN)	10.6	RIM REC	9.00
OD (IN)	28.7	RIM ALT	7.0
SLR (IN)	13.2	ECE	E11-106R-006010

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	57
5 FR	4480
15 FR	3800
20 FR	3580
25 FR	3200
5 DW	3180
15 DW	2700
20 DW	2545
25 DW	2270

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.