


AGRIMAX SPARGO

| | |
|---------------------|--|
| TIRE SIZE | VF 320/90 R 54 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRACTEUR |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 168 D |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|----------------------------|
| CODE USA | 94075249 | RC (IN) | 234.1 |
| SW (IN) | 12.7 | RIM REC | W 11 |
| OD (IN) | 76.7 | RIM ALT | W 10; DW 10; W 10 L; DW 11 |
| SLR (IN) | 35.8 | ECE | E11-106R-009070 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 14 | 17 | 20 | 23 | 26 | 29 | 32 | 35 | 38 | 41 | 44 | 47 | 49 | 52 | 55 | 58 | 61 | 64 |
|----------------------|------|------|------|------|------|------|------|------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 45 | 4920 | 5490 | 6180 | 6750 | 7090 | 7430 | 7670 | 7890 | 8290 | 8690 | 9030 | 9370 | 9660 | 9950 | 10230 | 10520 | 10970 | 11420 |
| FROM 40 TO 25 | 5320 | 5940 | 6670 | 7290 | 7670 | 8030 | 8280 | 8530 | 8960 | 9400 | 9760 | 10130 | 10440 | 10750 | 11060 | 11370 | 11870 | 12350 |
| 20 | 5430 | 6060 | 6820 | 7450 | 7820 | 8190 | 8450 | 8700 | 9140 | 9580 | 9960 | 10340 | 10650 | 10970 | 11280 | 11600 | 12110 | 12600 |
| 12 | 5530 | 6180 | 6950 | 7590 | 7970 | 8360 | 8610 | 8870 | 9320 | 9770 | 10160 | 10540 | 10860 | 11180 | 11500 | 11820 | 12340 | 12850 |
| 5 | 5850 | 6530 | 7350 | 8020 | 8430 | 8830 | 9110 | 9390 | 9860 | 10330 | 10740 | 11150 | 11490 | 11820 | 12160 | 12500 | 13040 | 13580 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.