


AGRIMAX RT 657

TIRE SIZE	540/65 R 38
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	MACHINE À VENDANGER / TRACTEUR / MOISSONNEUSE
VERSION	SPECIAL
TIRE TYPE	TL
LI/SS	153 D ; 156 A8



DIMENSIONS IS STANDARD

SW (MM)	530	RIM REC	W 16 L
OD (MM)	1667	RIM ALT	W 18 L
SLR (MM)	760	ECE	E4-106R-000589
RC (MM)	5059	SRI	800

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	1755	2045	2300	2555	2815	3030	3360	3650
50	1845	2150	2420	2685	2955	3185	3530	3835
40	1920	2240	2520	2800	3080	3320	3680	4000
30	2020	2355	2650	2940	3235	3490	3865	4200
10 LT	2350	2745	3085	3430	3770	4065	4505	4895
10 HT	2020	2355	2650	2940	3235	3490	3865	4200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.