


RIDEMAX FL 693 M



TIRE SIZE	710/50 R 26.5
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	CAMIÓN CISTERNA / REMOLQUE / MAQUINARIA AGRÍCOLA
VERSIÓN	STANDARD
TIRE TYPE	TL
LI/SS	170 D

DIMENSIONES IS STANDARD

SW (MM)	272	RIM REC	AG 24.00
OD (MM)	1383	RIM ALT	AG 20.00
SLR (MM)	624	ECE	E4-106R-001422
RC (MM)	4217	SRI	650

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	2020	2290	2780	3220	3710	4200	4525	5015	5450
65	2220	2520	3060	3540	4080	4620	4980	5520	6000
50	2690	3050	3705	4285	4940	5595	6030	6680	7260
40	3025	3430	4165	4815	5550	6285	6775	7510	8160
25	3510	3985	4835	5595	6450	7300	7870	8725	9480
10	4000	4540	5510	6375	7345	8320	8965	9940	10800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.