


# FL 630 ULTRA

|                     |  |
|---------------------|--|
| <b>TYRE SIZE</b>    | <b>600/50 R 22.5</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | TRAILER / IMPLEMENTS   |
| <b>VERSION</b>      | STANDARD   |
| <b>TYRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 159 D ; 170 A8   |



## DIMENSIONS US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94054220 | <b>RC (IN)</b> | 139.1           |
| <b>SW (IN)</b>  | 24.1     | <b>RIM REC</b> | AG 20.00        |
| <b>OD (IN)</b>  | 46.1     | <b>ECE</b>     | E11-106R-003960 |
| <b>SLR (IN)</b> | 20.4     |                |                 |

## LOAD CAPACITY (LBS/TYRE)

| MPH / PSI | 12   | 15   | 17   | 23   | 29    | 35    | 41    | 46    | 52    | 58    |
|-----------|------|------|------|------|-------|-------|-------|-------|-------|-------|
| 45        | 2820 | 3260 | 3690 | 4450 | 5190  | 5910  | 6660  | 7340  | 8090  | 8780  |
| 40        | 3090 | 3570 | 4060 | 4890 | 5700  | 6500  | 7300  | 8070  | 8870  | 9640  |
| 30        | 3740 | 4320 | 4910 | 5950 | 6890  | 7880  | 8820  | 9740  | 10750 | 11670 |
| 25        | 4230 | 4890 | 5560 | 6700 | 7800  | 8930  | 10040 | 11070 | 12170 | 13230 |
| 15        | 4880 | 5640 | 6400 | 7740 | 8990  | 10310 | 11490 | 12790 | 14030 | 15240 |
| 5         | 5560 | 6430 | 7300 | 8820 | 10250 | 11740 | 13090 | 14550 | 15970 | 17360 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.