


# AS 504

<b>TIRE SIZE</b>	<b>420/55 - 17</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	ELEVADOR TELESCÓPICO / EWMOLQUE PARA CAMPOS / MAQUINARIA AGRÍCOLA / ELEVADOR TELESCÓPICO
<b>VERSIÓN</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	133 A8
<b>LI/SS FREE ROLLING</b>	145 A8



## DIMENSIONES IS STANDARD

<b>SW (MM)</b>	430	<b>RIM REC</b>	13.00
<b>OD (MM)</b>	910	<b>ECE</b>	E11-106R-003302
<b>SLR (MM)</b>	407	<b>PR</b>	16
<b>RC (MM)</b>	2712		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	3.50
10 FR	4060
25 FR	3450
30 FR	3250
40 FR	2900
10 DW	2885
25 DW	2450
30 DW	2305
40 DW	2060

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.