


# FLOTATION 558

<b>TIRE SIZE</b>	<b>400/55 - 22.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	PRESSE À PAILLE / MOISSONNEUSE / VÉHICULE CITERNE / REMORQUE / MOISSONNEUSE / OUTILLAGE AGRICOLE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	138 A8/134 B
<b>LI/SS FREE ROLLING</b>	150 A8/146 B



## DIMENSIONS US STANDARD

<b>CODE USA</b>	94006243	<b>RC (IN)</b>	121.4
<b>SW (IN)</b>	15.9	<b>RIM REC</b>	AG 11.75
<b>OD (IN)</b>	40.2	<b>RIM ALT</b>	12.25; 13.00; AG 13.00
<b>SLR (IN)</b>	17.5	<b>ECE</b>	E4-106R-002261

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	44	46	51
<b>5 FR</b>	9450	9810	10340
<b>10 FR</b>	8500	8830	9300
<b>20 FR</b>	7550	7850	8270
<b>25 FR</b>	6750	7010	7390
<b>30 FR</b>	6070	6300	6610
<b>5 DW</b>	6650	6910	7290
<b>10 DW</b>	5990	6220	6560
<b>20 DW</b>	5320	5530	5830
<b>25 DW</b>	4750	4940	5200
<b>30 DW</b>	4280	4440	4670

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.