


# AGRIMAX FORTIS



<b>TIRE SIZE</b>	<b>600/70 R 34</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTOR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	160 D ; 163 A8

## DIMENSIONS US STANDARD

<b>USA CODE</b>	94035649	<b>RC (IN)</b>	201.1
<b>SW (IN)</b>	23.3	<b>RIM REC</b>	DW 18 L
<b>OD (IN)</b>	67.1	<b>RIM ALT</b>	DW 20 B; W 18 L
<b>SLR (IN)</b>	30.0	<b>ECE</b>	E4-106R-001401

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
40	4760	5560	6250	6940	7640	8230	9130	9920
30	5000	5840	6570	7300	8020	8650	9590	10420
25	5160	6020	6780	7530	8280	8930	9890	10750
20	5480	6390	7200	7990	8780	9480	10500	11410
5 LT	6380	7450	8380	9310	10240	11030	12230	13290
5 HT	5480	6390	7200	7990	8780	9480	10500	11410

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.