

# FLOTATION 558

<b>TIRE SIZE</b>	<b>400/55 - 22.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	EMPACADORA DE HENO / COSECHADORA / CAMIÓN CISTERNA / REMOLQUE / COSECHADORA / MAQUINARIA AGRÍCOLA
<b>VERSIÓN</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	140 A8/136 B
<b>LI/SS FREE ROLLING</b>	152 A8/148 B



## DIMENSIONES US STANDARD

<b>CÓDIGO USA</b>	94006250	<b>RC (IN)</b>	121.4
<b>SW (IN)</b>	15.9	<b>RIM REC</b>	AG 11.75
<b>OD (IN)</b>	40.2	<b>RIM ALT</b>	12.25; 13.00; AG 13.00
<b>SLR (IN)</b>	17.5	<b>ECE</b>	E4-106R-002262

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	54	55	58
5 FR	10460	10640	10960
10 FR	9410	9570	9870
20 FR	8370	8510	8760
25 FR	7470	7590	7830
30 FR	6720	6830	6940
5 DW	7370	7480	7720
10 DW	6640	6730	6940
20 DW	5900	5990	6170
25 DW	5270	5350	5510
30 DW	4740	4820	4940

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.