

# AS 504

<b>TIRE SIZE</b>	<b>270/75 - 16</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	111 A8
<b>LI/SS FREE ROLLING</b>	123 A8



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94053797	<b>ECE</b>	E11-106R-004241
<b>SW (IN)</b>	9.8		
<b>OD (IN)</b>	31.9		
<b>RIM REC</b>	9.00		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	57
5 FR	4780
15 FR	4070
20 FR	3820
25 FR	3420
5 DW	3360
15 DW	2850
20 DW	2690
25 DW	2400

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.