

RIDEMAX FL 693 M

TIRE SIZE	560/55 R 22.5
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	АВТОЦИСТЕРНА / ПРИЦЕП / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	158 D ; 155 E



РАЗМЕРЫ IS STANDARD

SW (MM)	543	RIM REC	AG 16.00
OD (MM)	1180	RIM ALT	17.00 ; 20.00
SLR (MM)	533	ECE	E4-106R-000631
RC (MM)	3614	SRI	550

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1435	1630	1940	2290	2620	2910	3255	3565	3875
65	1575	1785	2125	2510	2870	3190	3570	3910	4250
50	1910	2165	2575	3040	3475	3860	4325	4735	5145
40	2140	2430	2890	3415	3905	4335	4860	5320	5780
25	2490	2825	3360	3965	4535	5040	5645	6180	6715
10	2835	3215	3825	4515	5165	5740	6430	7040	7650

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.