

# AGRIMAX RT 765

<b>TIRE SIZE</b>	<b>600/70 R 30</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	IRRORAZIONE / TRATTORE / VENDEMMIATRICE / MIETITREBBIA / ATTREZZI AGRICOLI
<b>VERSIONE</b>	SPECIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	152 D



## DIMENSIONI US STANDARD

<b>CODICE USA</b>	94062331	<b>RC (IN)</b>	188.0
<b>SW (IN)</b>	24.1	<b>RIM REC</b>	DW 20 B
<b>OD (IN)</b>	63.1	<b>RIM ALT</b>	DW 18 L; W 18 L
<b>SLR (IN)</b>	28.0	<b>ECE</b>	E11-106R-005523

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
40	4310	5020	5720	6430	7130	7830
30	4530	5270	6010	6750	7480	8220
25	4720	5490	6260	7030	7800	8580
20	4960	5760	6580	7390	8200	9010
5 LT	5780	6720	7660	8610	9560	10490
5 HT	4960	5760	6580	7390	8200	9010

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.