


RIDEMAX FL 693 M



TYRE SIZE	560/55 R 22.5
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TANKER / TRAILER / IMPLEMENTS
VERSION	STANDARD
TYRE TYPE	TL
LI/SS	158 D ; 155 E

DIMENSIONS US STANDARD

USA CODE	94037353	RC (IN)	142.3
SW (IN)	21.4	RIM REC	AG 16.00
OD (IN)	46.5	RIM ALT	17.00; 20.00
SLR (IN)	21.0	ECE	E4-106R-000631

LOAD CAPACITY (LBS/TYRE)

MPH / PSI	15	17	23	29	35	41	46	52	58
45	3160	3590	4280	5050	5780	6420	7180	7860	8540
40	3470	3940	4680	5530	6330	7030	7870	8620	9370
30	4210	4770	5680	6700	7660	8510	9530	10440	11340
25	4720	5360	6370	7530	8610	9560	10710	11730	12740
15	5490	6230	7410	8740	10000	11110	12440	13620	14800
5	6250	7090	8430	9950	11390	12650	14170	15520	16860

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.