



IS standard



GROWING TOGETHER

TR 678 IND



PRODUCT DATA SHEET



Bias



A8



169

Technologies



More Lugs



Steel Belted



Strong Casing

Performance



Cut and Chip Resistance



High Load Capacity



High Puncture Resistance



Self-Cleaning



Traction



TR 678 IND

TR 678 IND has been specially designed for industrial applications. Its robust lug design provides excellent traction and self-cleaning. The strong casing structure stands for high load capacity whereas its steel belts protect the tire from punctures and damages. TR 678 features a cut-resistant tread compound providing excellent cut-and-chip resistance even on difficult terrains under extreme conditions.

	Tire size	Type	PR	LI/SS		Version	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
				DW	FR						Rec.	Alt.
Ø 22.5"	600/40 - 22.5	TL	-	157 A8	169 A8	DB	615	1085	483	3264	AG 20.00	-

DB: Dual Bead



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; DW = Drive Wheel; FR = Free Rolling