

AGRIMAX V-FLECTO

TIRE SIZE	VF 520/60 R 28
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRACTOR DE ALTA POTENCIA / TRACTOR
VERSIÓN	STANDARD
TIRE TYPE	TL
LI/SS	149 D



DIMENSIONES US STANDARD

CÓDIGO USA	94060733	RC (IN)	153.9
SW (IN)	20.3	RIM REC	DW 18 L
OD (IN)	52.6	RIM ALT	W 18 L
SLR (IN)	23.1	ECE	E11-106R-005497

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
45	3570	4170	4750	5350	5920	6510
FROM 40 TO 25	3940	4590	5220	5870	6510	7165
20	4010	4670	5320	5990	6640	7310
12	4090	4760	5420	6110	6770	7450
5	4320	5040	5740	6460	7160	7880
*UPTO 5 CYC WITH FRONT LOADER	5500	6420	7310	8220	9120	10030
5 HT	4010	4670	5320	5990	6640	7310

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.