

# TF 8181

|                     |                                 |
|---------------------|---------------------------------|
| <b>TIRE SIZE</b>    | 11.00 - 16                      |
| <b>UM</b>           | US STANDARD                     |
| <b>CONSTRUCTION</b> | BIAS                            |
| <b>MACHINERY</b>    | TRACTOR 2WD / TRACTOR / REMORCĂ |
| <b>VERSION</b>      | STANDARD                        |
| <b>TIRE TYPE</b>    | TT                              |
| <b>LI/SS</b>        | 114 A8                          |



## DIMENSIUNI US STANDARD

|                 |          |                |                |
|-----------------|----------|----------------|----------------|
| <b>USA CODE</b> | 94032761 | <b>RC (IN)</b> | 115.0          |
| <b>SW (IN)</b>  | 12.8     | <b>RIM REC</b> | W 10 L         |
| <b>OD (IN)</b>  | 38.2     | <b>RIM ALT</b> | W 8; W 8 L     |
| <b>SLR (IN)</b> | 17.6     | <b>ECE</b>     | E4-106R-002673 |

## LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>40</b> |
| 25               | 2600      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.