

AGRIMAX V- FLECTO

VF 600/70 R 28 NRO

UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	YÜKSEK GÜÇTE TRAKTÖR / TRAKTÖR
VERSION	STANDARD
TIRE TYPE	TL
	167 D



UNDEFINED US STANDARD

USA CODE	94074815	RC (IN)	180.9
SW (IN)	23.7	RIM REC	DW 21 B
OD (IN)	61.1	RIM ALT	DW 20 B
SLR (IN)	26.1	ECE	E11-106R-008814

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29
45	5350	6220	7210	8080	8950	9820	10920
FROM 40 TO 25	5890	6840	7930	8880	9840	10810	12010
20	6000	6980	8080	9060	10040	11010	12250
12	6120	7110	8230	9240	10240	11230	12490
5	6470	7530	8720	9780	10840	11890	13220
*UPTO 5 CYC WITH FRONT LOADER	8230	9580	11100	12440	13790	15130	16820
5 HT	6000	6980	8080	9060	10040	11010	12250

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.